

EB GUIDE tutorial

Using image-based lighting Version 6.7.3.150087

Copyright © 2019 Elektrobit Automotive GmbH

Legal notice

Confidential and proprietary information

ALL RIGHTS RESERVED. No part of this publication may be copied in any form, by photocopy, microfilm, retrieval system, or by any other means now known or hereafter invented without the prior written permission of Elektrobit Automotive GmbH.

All brand names, trademarks and registered trademarks are property of their rightful owners and are used only for description.



1. Tutorial: Using image-based lighting

NOTE

Default window layout



All instructions and screenshots of this user's guide use the default window layout. If you want to follow the instructions, we recommend to set the EB GUIDE Studio window to default layout by selecting **Layout > Reset to default layout**.

The following instructions guide you through the process of using image-based lighting for scene graphs in EB GUIDE Studio.

Approximate duration: 10 minutes.



Accessing IBLGenerator help instructions

In the following steps, you start IBLGenerator.

Step 1

With the help of command line, navigate to the directory that contains the executable IBLGenerator.exe.

For example, C:/Program Files/Elektrobit/EB GUIDE Studio 6.7/platform/win32

Step 2

Enter IBLGenerator.exe -h.

All options of the IBLGenerator are listed.



Generating an .ebibl file

Prerequisite:

- You completed the previous instruction.
- You have a .pfm file as input data.

Step 1

Enter a command with your desired parameters according to the IBLGenerator help.

For example:

This command executes the IBLGenerator with the input file MyInputFile.pfm which stores its data in cube parameterization. The quality level is set to 3 and the result is stored in MyOutputFile.ebibl.





Applying image-based lighting

Prerequisite:

- You completed the previous instruction.
- The .ebibl file is generated by using the IBLGenerator.
- The .ebibl file is placed within the resources directory of the current project.
- A project is opened in EB GUIDE Studio.
- A view state is added.
- A scene graph is added and a 3D file is imported.

Step 1

Add an image-based light to a scene graph node of the imported scene graph.

Step 2

Go to the **Properties** component.

Step 3

From the ibl drop-down box, select MyOutputFile.ebibl as input.

Step 4

For best results, adapt the properties of the image-based light and use PBR GGX material or PBR Phong material.

To only illuminate the scene with image-based lighting, disable all other light sources.

If more than one image-based light is added to a scene graph, only the first one in the hierarchy influences the scene.

NOTE

Image-based lighting in OpenGL ES 2.0



To use image-based lighting, the OpenGL ES 2.0 driver has to support the OpenGL extensions GL_EXT_shader_texture_lod, GL_EXT_texture_rg, GL_OES_texture_float, and GL_OES_texture_half_float if you use the OpenGL renderer.

If you use the DirectX renderer and OpenGL 3 renderer, image-based lighting is always supported.